



MECT
mechatronic thinking

AVAILABLE MODELS:

MP45 P6

+39 011 966 46 16

sales@mect.it
srlmect@mect.it



A - Model

MP45VD = Vdc inputs
MP45VA = Vac inputs
MP45AD = Adc inputs
MP45AA = Aac inputs
MP45PO = Potentiometer input

B - Measuring scales

<i>Mod. MP45VD</i>	<i>Mod. MP45VA</i>	<i>Mod. MP45AD</i>	<i>Mod. MP45AA</i>
01 = 199.9mVdc	01 = 199.9mVac*	01 = (0)4÷20mAdc	01 = 1.999mAac*
02 = 1.999Vdc	02 = 1.999Vac*	02 = 1.999mAdc*	02 = 19.99mAac*
03 = 19.99Vdc	03 = 19.99Vac*	03 = 19.99mAdc*	03 = 199.9mAac*
04 = 199.9Vdc	04 = 199.9Vac*	04 = 199.9mAdc*	04 = 1.999Aac*
05 = 300Vdc	05 = 300Vac*	05 = 1.999Adc*	05 = 9.99Aac*
06 = 0÷1Vdc	06 = 0÷1Vac*	06 = 9.99Adc*	06 = T.A./1Aac
07 = 0÷10Vdc	07 = 0÷10Vac*	07 = shunt ext.*	07 = T.A./5Aac
08 = 0÷100Vdc	08 = 0÷100Vac*		

For inputs 600Vac/Vdc specify **μ188** option

C - Power supply

110 = 115 Vac
220 = 230 Vac
24 = 25 Vac
VCC = 12÷30 Vdc
VPT = 12÷30 Vdc optoisolated

D - Alarms

SR1 = 1 relay alarm
SR2 = 2 relay alarms

*DC power supply will be opto-isolated